

helmets & accessories

apparel

accessories

carriers & racks

bumpers & winches

plogs

frame & chassis

body

handlebar

cables & levers

engine

fuel & intake

electrical & ignition

clutch

drive

bearings

brakes

suspension & steering

tires & wheels

chemicals

tools

towing & loading

go cart

WARN

RT15
RUGGED TERRAINRT 15 & XT 15
PERFORMANCE SPECS:XT15
EXTREME TERRAIN

LINE PULL		LINE SPEED		MOTOR CURRENT		PULL BY LAYER	
lbs.	kgs.	ft./min	m/min	amps		layer/lbs.	kgs.
0		15	4.6	6		1/1500	680
500	227	11	3.3	27		2/1320	599
1000	455	7	2.1	44		3/1162	527
1500	680	5	1.5	65		4/1020	463

BASED ON THE FIRST LAYER OF DRUM

RT15
RUGGED TERRAINPART NUMBER: **WR78000** \$310.55

With 1,500 lbs. of pulling power, this winch is great for getting a stuck sport quad or small ATV out of a sticky situation. Standard features include a sealed 0.4hp motor; 50' of 5/32" diameter aircraft-grade wire rope; a potted-and-sealed mini-rocker handlebar control; a compact waterproof contactor; and a hawse fairlead.

SPECIFICATIONS

Rated Line Pull:	1500 lbs (680 kgs)
Motor:	12V DC, 0.4HP Permanent Magnet, Sealed
Control:	Handlebar Mounted Mini-rocker Switch
Gear Train:	3-Stage Planetary
Gear Ratio:	103:1
Clutch (freespooling):	Cam activated
Brake:	Mechanical Brake Standard
Drum Diameter / Length:	1.5" / 3.0"
Fairlead:	Hawse
Wire Rope:	50' Aircraft-Grade Wire, 5/32" diameter (15m, 4mm diam.)
Recommended Battery:	12 AMP / Hour Minimum
Battery Leads:	10 Gauge
Duty Cycle:	Intermittent
Warranty:	Limited Lifetime
Mounting Bolt Pattern:	3.0" x 4.88" (76 x 124mm)
Winch Dimensions:	10.3" L x 3.0" D x 4.56" H (26cm L x 10cm D x 11.6cm H)
Winch Weight:	11.5 LBS. (5.2 kgs)

XT15
EXTREME TERRAINPART NUMBER: **WR78500** \$339.25

This is the top-of-the-line 1,500 lb. light-duty winch perfect for sport quads or small ATVs. It comes standard with 50' of 5/32" synthetic rope for light weight and easy handling; a sealed 0.4hp motor; a potted-and-sealed mini-rocker handlebar control; a compact waterproof contactor; and a roller fairlead.

SPECIFICATIONS

Rated Line Pull:	1500 lbs (680 kgs)
Motor:	12V DC, 0.4HP Permanent Magnet, Sealed
Control:	Handlebar Mounted Mini-rocker Switch
Gear Train:	3-Stage Planetary
Gear Ratio:	103:1
Clutch (freespooling):	Cam activated
Brake:	Mechanical Brake Standard
Drum Diameter / Length:	1.5" / 3.0"
Fairlead:	Roller
Wire Rope:	50' Synthetic, 5/32" diameter (12.2m, 4mm diam.)
Recommended Battery:	12 AMP / Hour Minimum
Battery Leads:	10 Gauge
Duty Cycle:	Intermittent
Warranty:	Limited Lifetime
Mounting Bolt Pattern:	3.0" x 4.88" (76 x 124mm)
Winch Dimensions:	10.3" L x 3.0" D x 4.56" H (26cm L x 10cm D x 11.6cm H)
Winch Weight:	8.6 LBS. (3.9 kgs)



Small Engine Discount
Phone: 1-904-291-1100
Fax: 1-904-291-1788

Parts@SmallEngineDiscount.com

